



Lightweight Solar

LWS430-60CW

LWS435-60CW

LWS440-60CW

LWS445-60CW

LWS450-60CW




Product and Quality Certifications

IEC 61215, IEC 61730

ISO 9001 : 2015 Quality Management System

ISO 14001 : 2015 Environment Management System



Lightweight

Optimized composite materials, 70% lighter at the same power.



Flexible

Flexional encapsulating and patent materials.



Excellent Appearance and Performance

Esthetics module design, no flare effect, "0" risk of micro crack.



Easy transportation and installation

Original design making it far less costly for transportation and installation.



Customization

Customization for various scenarios, high additional value.



Superior Performance at Low Irradiance

Excellent low irradiance performance, increase power generation in low-light conditions like mornings, evenings and cloudy days.

S.flexTM Ultra Light Flexible PV Module

450W


Maximum Output Power

20.70%

Maximum Module Efficiency

0~+5W

Power Output Tolerance



Electrical Data (STC)

Part Number	LWS430-60CW	LWS435-60CW	LWS440-60CW	LWS445-60CW	LWS450-60CW
Peak Power Watts- $P_{MAX}(Wp)^*$	430	435	440	445	450
Power Output Tolerance	0/+5W				
Open Circuit Voltage- $V_{oc}(V)$	41.43	41.58	41.73	41.88	42.03
Short Circuit Current- $I_{sc}(A)$	13.62	13.69	13.76	13.83	13.90
Maximum Power Voltage- $V_{MPP}(V)$	34.18	34.33	34.48	34.63	34.78
Maximum Power Current- $I_{MPP}(A)$	12.30	12.68	12.77	12.86	12.95
Panel Efficiency(%)	19.80	20.00	20.30	20.50	20.70

STC :Irradiance 1000w/m², Cell Temperature 25°C *Mearsure tolerance:±3%

Electrical Data (NMOT)



MaximumPower- $P_{MAX}(Wp)^*$	320	324	327	331	335
Open Circuit Voltage- $V_{oc}(V)$	38.60	38.75	38.89	39.03	39.17
Short Circuit Current- $I_{sc}(A)$	10.99	11.05	11.11	11.16	11.22
Maximum Power Voltage- $V_{MPP}(V)$	32.40	32.54	32.68	32.82	32.96
Maximum Power Current- $I_{MPP}(A)$	9.88	9.96	10.01	10.09	10.16

NMOT:Irradiance at 800W/m², Ambient Temperature 20°C, Wind Speed 1m/s

Mechanical Data

Panel Dimension	1911 x 1137 mm
Thickness	3.4mm±0.2
Weight	9 kg
Cell Size	182x91 mm
Cell Number	120
Junction Box Diodes	3
Junction Box Protection Class	IP68
Connector Type	MC4 or MC 4 Compatible
Cable	1x4mm ² ,(+): 300mm , (-): 300mm or Customized Length

Dimensions of PV Module(mm)



Temperature Ratings

NMOT	45°C(±2°C)
Temperature Coefficient of P_{MAX}	-0.350%/°C
Temperature Coefficient of V_{oc}	-0.260%/°C
Temperature Coefficient of I_{sc}	+0.047%/°C

* Do not connect Fuse in Combiner Box with two or more strings in parallel connection

Maximum Ratings

Operational Temperature	-40~±85 °C
Front/Rear Side Load	2400/2400pa
Max Series Fuse Rating	25A
Max System Voltage	1500V (DC)

Packaging Configuration

Modules per box	68 pieces
Modules per 40'container	1632 pieces

Warranty

Product Workmanship Warranty	15 years
Output Power Warranty	25 years